

BAKKEN 88 SPECIALTY

| Parameter | Value | Unit | |
|-----------------|-------|------|--|
| Moisture | 4.5 | % | |
| Friability | 86.1 | % | |
| Extract FGDB | 80.2 | % | |
| Extract CGDB | 78.5 | % | |
| F-C Difference | 1.71 | % | |
| Color | 88 | SRM | |
| Beta Glucan | 226 | Mg/L | |
| Soluble Protein | 6.33 | % | |
| Total Protein | 11.7 | % | |
| S/T | 54.1 | % | |
| FAN | 73 | Mg/L | |
| DP | 46 | L | |
| Alpha Amylase | 29 | D.U. | |
| Filtration | Slow | Time | |
| Turbidity | | NTU | |
| рН | 5.02 | | |
| Plumps on 6/64 | 96.1 | % | |
| Thins on 5/64 | 0.8 | % | |





GRAIN HISTORY

This malt was made from Buzz two-row barley that was delivered by Arrow K Farms. Arrow K Farms is located in Belfield, ND just a few miles east of Theodore Roosevelt National Park in western ND.

Two Track Malting uses grain grown without irrigation by growers practicing regenerative agriculture. This results in the highest quality grain grown with the least environmental impact.

Hot Steep Method

<u>Items Needed to perform the Hot Steep Method:</u>

24-ounce Thermos Funnel Cone Coffee Filter Coffee Grinder

Scale capable of weighing 50.0 g (\pm 0.1 g) Glass Beaker, tall, 600 mL volume Thermometer, standard, 0-200°C

Quart sized large or small mouth canning jars Heating apparatus, capable of heating water to 65°C

Steps to perform the Hot Steep Method:

- 1. Grind 50.0g of malt in coffee grinder (grind of 10-15 sec)
- 2. Add 400ml of 65°C (149°F) water to Thermos
- 3. Add grist to water, cap thermos and shake for 20 \mbox{sec}
- 4. Let rest for 15min
- 5. When timer is up, swirl for a few seconds then poor everything into filter in funnel over large jar
- 6. Collect 100ml of wort and add it back into filter
- 7. Collect and Taste

Check Your Malt Grind

Take 100g of milled grist and Place in #14 Sieve stacked over #30,#60 over pan, Slide 18" on smooth surface for 3 min and Tap sharply on surface ever minute Record Grist retained above in each sieve Chart to the below gives Percentage of what should be retained in each sieve for each grind

| 100g Sample | #14 Sieve | #30 Sieve | #60 Sieve | Pan |
|--------------|-----------|-----------|-----------|-----|
| Coarse Grind | 78g | 14g | 4g | 4g |
| Medium Grind | 53g | 28g | 11g | 8g |
| Fine Grind | 25g | 25g | 30g | 20g |

Calculating PPG and OG

PPG (SG of 1 lb of fermentable in 1 gal of water)

PPG=46.214*(DBCG/100-MC%/100-0.002)

Original Gravity Calculation

OG=1+(EF%/100)*(PPG*MW/BV)

MW = pounds of malt used BV = Batch volume in gallons EF% = Mashing efficiency OG = Original Gravity PPG = Pounds Per Gallon MC = Moisture Content DBCG = Course Grind Extract